













LamWood 8mm Technical Information











Usage	Result
 Product Reference	Boracay
 Size (L x W x Thickness) mm	1215 x 195 x 8
 Board Type	Drop-Loc system
 Pattern	1 strip
 Structure	Carb 2 HDF core
 Edging	Bevelled
 Pack Size	2.369m ²
 Pack weight	18kg
 Pack length	1215mm, 10 full length boards per pack
 Surface finish	AC5 Heavy Commercial
 Environmental rating	A+. Green Building Council of Australia: Pass
 Maintenance	As per maintenance instruction- refer website www.terramaterfloors.com.au

Installation Methods

 Fully bonded	No
 Nailed	No
 Floated inderlay	Yes*
 Over under slab heating	Yes

*Subject to compatible subfloor and correct installation (Refer Installation Instructions)

Test Information & Others













 Origin	China
 Abrasion AS/NZS 4266.20: 2004	AC5 Heavy commercial
 Slip testing	AS/NZS 4586-2004 Wet: P2, Dry: D1
 Australian reaction to fire- FLOOR	ASISO 9239-1:2003 CRF 5.2kw/m ² , smoke value 5%
 Australian reaction to fire- WALL	Not applicable
 Swell Test AS/NZS 4266.8:2004	0% swell (max limit 15%) after 24hr immersion
 Release of formaldehyde	ASTM D5116 0.008mg/m ² /hr (max limit allowable 0.1)
 Release of 4-phenylcyclohexene	ASTM D5116 <0.005mg/m ² /hr (max limit allowable 0.05)
 Total VOC	ASTM D5116 0.005mg/m ² /hr (max limit allowable 0.5mg/m ² /hr)
 Warranty- Domestic	25 Year Wear and Lifetime structural
 Warranty- Commercial	5 Year Wear and Lifetime structural

Installation & Warranty

All LamWood floors must be installed by a competent approved installer who will have the necessary skills and take individual site circumstance into account. LamWood warranty will only apply to floors which have been installed according to the LamWood installation instructions available in each box of LamWood and also on the TerraMater website - terramaterfloors.com.au

Please note this technical sheet was written by TerraMater Floors Pty Ltd, All the information is specified correctly while writing and publication of the sheet. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

LamWood 12mm Technical Information












	Usage	Result
	Product Reference	Lamwood
	Size (L x W x Thickness) mm	2200 x 193 x 12
	Board Type	Drop-Loc system
	Pattern	1 strip- no pattern repeat in length of board. 6 pattern repeats within the floor system
	Structure	Carb 2 HDF core
	Edging	Bevelled
	Pack Size	1.698m ²
	Pack weight	18kg
	Pack length	2200mm, 4 full length boards per pack
	Surface finish	EIR Registered Embossed / Matt finish
	Environmental rating	A+. Green Building Council of Australia: Pass
	Surface Wear Rating	AC5 Heavy Commercial

Installation Methods

	Fully bonded	No
	Nailed	No
	Floated underlay	Yes*
	Over under slab heating	Yes*

*Subject to compatible subfloor and correct installation (Refer Installation Instructions)

Test Information & Others

	Origin	China
	Abrasion AS/NZS 4266.20: 2004	AC5 Heavy commercial
	Slip testing	AS/NZS 4586-2004 Wet: P2, Dry: D1
	Australian reaction to fire- FLOOR	ASISO 9239-1:2003 CRF 5.2kwm ² , smoke value 5%
	Australian reaction to fire- WALL	Not applicable
	Swell Test AS/NZS 4266.8:2004	0% swell (max limit 15%) after 24hr immersion
	Release of formaldehyde	ASTM D5116 0.008mg/m ² /hr (max limit allowable 0.1)
	Release of 4-phenylcyclohexene	ASTM D5116 <0.005mg/m ² /hr (max limit allowable 0.05)
	Total VOC	ASTM D5116 0.005mg/m ² /hr (max limit allowable 0.5mg/m ² /hr)
	Warranty- Domestic	25 Year Wear and Lifetime structural
	Warranty- Commercial	5 Year Wear and Lifetime structural

Installation & Warranty

All LamWood floors must be installed by a competent approved installer who will have the necessary skills and take individual site circumstance into account. LamWood warranty will only apply to floors which have been installed according to the LamWood installation instructions available in each box of LamWood and also on the TerraMater website - terramaterfloors.com.au

Please note this technical sheet was written by TerraMater Floors Pty Ltd, All the information is specified correctly while writing and publication of the sheet. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.