

# RIGIDCORE.

977

Summit Collection

Co Extrusion Technology



## Technical Information

Dimensions	1820 x 225mm	Finish/Gloss	Matte
Total Thickness	9.7mm	Guarantee	30 years domestic, 15 years commercial
Core Thickness	7.0mm	Profile Edge	Micro Bevel
Wear Layer	0.7mm	Classification	Rigid Core
Backing	EVA 2.0mm	Core	Co Extrusion Technology
Box Quantity	1.638sqm, 4 planks per box	Colours	10
		Installation	5G Click

## Performance

	Standard	Result
Reaction to Fire	EN ISO 9239-1:2010	10.5km/sqm, 298.2% minimum smoke
Slip Resistance	BS7976-2:2002+A1:2013	PTV Dry: 56 PTV Wet: 35
Staining Resistance	ISO26987:2008	0 not affected
Colour Fastness	ISO105-B02:2014 method 3	Grade 6
Abrasion Resistance	EN660-2:1999+A1 and EN649:2011	Wear Group T
Dimensional Stability		
Thermal Conductivity		
Thermal Resistance		
Acoustic Reduction	ISO10140-1:2016	Lw = 20db (delta IIC)
Adhesive	none- 5G click system	
Recycling	n/a	
Environmental	Green Building Council Compliant for VOC	
Swell Test		

# Why should you choose Resiplank boards



## Waterproof

Resiplank's waterproof floors stand up to spills of all sizes.



## Children Friendly

Resiplank floors offer kids a safe and comfortable space to play and parents a durable, easy-to-clean surface.



## Pet Friendly

From muddy paw prints to household accidents and anything in-between, Resiplank's low-maintenance floors are designed with pets in mind.



## Lifetime Warranty

Not only is a Resiplank floor unique to your home, but it is guaranteed to last for years to come.



## Durable

Resiplank boards are extremely hardwearing. Unlike real wood and stone, it won't splinter, warp or crack.




## Comfort

Softer and warmer underfoot than natural wood flooring. Additional cushioning in the backing helps make the product more comfortable.




## Low Maintenance

We use PU technology to ensure that there is no need to apply an additional surface treatment following installation.



## Compatible with Underfloor Heating

Up to 27°C.



## 100% Recyclable

We use PU technology to ensure that there is no need to apply an additional surface treatment following installation.



## Individually Replaceable

Should you need to replace a piece, simply lift the damaged plank and replace with a new one.



## Quick and Easy to Install

All you need is a sound, smooth, dry and dust free subfloor. Resiplank can be fitted over most existing hard floors.



## Acoustic Qualities

Perfect for projects where you want to reduce noise levels in the room below, without the need for underlay.