

Technical Data

Attributes	Standard	Result
Type of floor covering		Hybrid / Rigid Core
Installation		5G® Click
Core		SPC
Colours		10
Size		1820 x 180 mm
Thickness		7.0 mm
Core thickness		5 mm
Wear layer		0.5 mm
Surface treatment		PU coating
Backing		1.5 mm EVA underlay
Packaging		6 planks / pack = 1.996 m ²
Total weight		10.19 kg/m ² / 20.04 kg per pack
Beveled edge		4 sided micro bevel
Classification	ISO 10874 / EN 685 ISO 10874 / EN 685	Commercial: light Domestic: heavy
Reaction to fire	AS/NZ ISO9239 1-2003	CHF: ≥11 k@/m ² Smoke Value: 136% -min
Slip resistance	AS/NZS 4586.2013 Wet pendulum	SRV 30 / P2
Dimensional stability	Heat at 60 °C for 24 hours	Length: -0.11% Width: -0.09%
Acoustic impact noise reduction	AS/NZ ISO 717.2-2004	F _{LIC} ^{4,5} = 66 L'nTw ³ = 43 AAAC 5 Star Rating
Underfloor heating		Suitable for hydronic underfloor heating, max. 27°C
Environmental	ASTM D5116-17 Green Building Council of Australia Phthalate Free	Compliant for VOC Yes
Quartz content (wt%)		Not detected
Warranty*	Commercial Domestic	10 years wear 25 years wear

*Please refer to Terra Mater Floors warranty information for guidance. www.terramaterfloors.com.au

[†]Please refer to www.terramaterfloors.com.au for results.



Terra Mater Floors

23-27 Rodeo Drive, Dandenong South VIC 3175 Australia | 1300 671 777 | info@terramaterfloors.com.au | www.terramaterfloors.com.au