

# Technical Data

Attributes	Standard	Result
Type of floor covering		Hybrid / Rigid Core
Installation		5G® Click
Core		SPC
Colours		10
Size		1420mm x 225mm
Thickness		8.5mm
Core thickness		6.0mm
Wear layer		0.5mm
Surface treatment		PU coating
Backing		2.0mm EVA underlay
Packaging		6 Planks / pack = 1.917m <sup>2</sup>
Total weight		12.57kg/m <sup>2</sup> / 24.10kg per pack
Beveled edge		4 sided micro bevel
Classification	ISO 10874 / EN 685 ISO 10874 / EN 685	Commercial: light Domestic: heavy
Reaction to fire	AS/NZ ISO9239 1-2003	CHF: 9.3kW/m <sup>2</sup> Smoke value: 207%.min
Slip resistance	AS 4586-2013 Amdt 1-2017 Appendix A	SRV 37 / P3
Dimensional stability	Heat at 60°C for 24 hours	Length: -0.15% Width: -0.15%
Acoustic impact noise reduction	AS/NZ ISO 717.2-2004	FIIC <sup>4,5</sup> = 62 L'nTw <sup>3</sup> = 42 AAAC 5 Star Rating <sup>1</sup>
Underfloor heating		Suitable for hydronic underfloor heating, max. 27°C
Environmental	ASTM D5116-17 Green Building Council of Australia Phthalate Free	Compliant for VOC  Yes
Quartz content (wt%)		Not detected
Warranty	Commercial Domestic	10 Year wear* 25 Year wear*

\*Please refer to Terra Mater warranty information for guidance. [www.terramaterfloors.com.au](http://www.terramaterfloors.com.au)

<sup>1</sup>Please refer to [www.terramaterfloors.com.au](http://www.terramaterfloors.com.au) for results.



**8 Design**  
Repeat



**Registered / Natural**  
Emboss



**2.0mm**  
Acoustic Underlay



**100%**  
Waterproof



## Terra Mater

23-27 Rodeo Drive, Dandenong South VIC 3175 Australia | 1300 671 777 | [sales@terramaterfloors.com.au](mailto:sales@terramaterfloors.com.au) | [www.terramaterfloors.com.au](http://www.terramaterfloors.com.au)