

# Technical Data

Attributes	Standard	Result
Type of floor covering		Hybrid / Rigid Core
Installation		5G® Click
Core		SPC
Colours		10
Size		1820mm x 180mm
Thickness		7.0mm
Core thickness		5.0mm
Wear layer		0.5mm
Surface treatment		PU coating
Backing		1.5mm EVA underlay
Packaging		6 Planks / pack = 1.996m <sup>2</sup>
Total weight		10.19kg/m <sup>2</sup> / 20.95kg per pack
Beveled edge		4 sided micro bevel
Classification	ISO 10874 / EN 685 ISO 10874 / EN 685	Commercial: light Domestic: heavy
Reaction to fire	AS/NZ ISO9239 1-2003	CHF: ≥11kW/m <sup>2</sup> Smoke value: 136%.min
Slip resistance	AS 4586-2013 Amdt 1-2017 Appendix A	SRV 37 / P3
Dimensional stability	Heat at 60°C for 24 hours	Length: -0.11% Width: -0.09%
Acoustic impact noise reduction	AS/NZ ISO 717.2-2004	FIIC <sup>4,5</sup> = 66 L'nTw <sup>3</sup> = 43 AAAC 5 Star Rating <sup>1</sup>
Underfloor heating		Suitable for hydronic underfloor heating, max. 27°C
Environmental	ASTM D5116-17 Green Building Council of Australia Phthalate Free	Compliant for VOC  Yes
Quartz content (wt%)		Not detected
Warranty	Commercial Domestic	10 Year wear* 25 Year wear*

\*Please refer to Terra Mater warranty information for guidance. [www.terramaterfloors.com.au](http://www.terramaterfloors.com.au)

<sup>1</sup>Please refer to [www.terramaterfloors.com.au](http://www.terramaterfloors.com.au) for results.



**5 Design**  
Repeat



**Registered / Natural**  
Emboss



**1.5mm**  
Acoustic Underlay



**100%**  
Waterproof



## Terra Mater

23-27 Rodeo Drive, Dandenong South VIC 3175 Australia | 1300 671 777 | [sales@terramaterfloors.com.au](mailto:sales@terramaterfloors.com.au) | [www.terramaterfloors.com.au](http://www.terramaterfloors.com.au)