## **Technical Data**

Attributes	Result
Species	European Oak
Size (L x W x Thickness/top) mm	1900mm x 190mm X 14mm/3mm
Locking system	Tongue & Groove
Pattern	1 Strip
Core	Multiply core
Edging	4 sided micro bevel
Pack size	2.888m <sup>2</sup>
Pack weight	28kg
Pack length	1900mm, 8 boards per pack, up to 25% nesting per pack
Top layer (lamella)	3mm European Oak
Surface finish	10% matte UV lacquer
Installation	Floating / Direct stick
Adhesive	Swedish Dynea
Installation Methods	
Fully bonded	Yes*
Nailed	No
Floated underlay	Yes*
Over under slab heating	Yes*
*Subject to compatible subfloor and correct inst	allation (Refer Installation Instructions)
<b>Test Information &amp; Others</b>	
Origin	Europe
EUTR	Legally harvested timber
FSC	Not available

WildOak

BY **TERRA MATER** Origins 190mm

FSC	Not available
Janka hardness rating	1360 LBF (7.0)
Slip testing	AS/NZS 4586-2004 Wet: P3, Dry: D1
Australian reaction to fire (Floor)	ASISO 9239-1:2003 CRF 3.6kwm <sup>2</sup> , smoke value 19%
Australian reaction to fire (Wall)	AS/NZS 3837:1998 58.3kw/m²
Cigarette burns	Repairable
Release of formaldehyde	ASTM D51166 0.093mg/m²/hr (max limit allowable 0.1)
Release of 4-phenylcyclonexene	ASTM D5116 <0.004mg/m²/hr (max limit allowable 0.05)
Total VOC	ASTM D5116 0.016mg/m²/hr (max limit allowable 0.5mg/m²/hr)
Environmental rating	A+. Green Building Council of Australia: Pass
Warranty (Domestic)	20 Year wear and lifetime structural
Warranty (Commercial)	10 Year wear and lifetime structural

## Installation & Warranty

All WildOak floors must be installed by a competent approved installer who will have the necessary skills and take individual site circumstance into account. WildOak warranty will only apply to floors which have been installed according to the WildOak installation instructions available in each box of WildOak and also on the TerraMater website terramaterfloors.com.au

Please note this technical sheet was written by TerraMater Pty Ltd, All the information is specifield correctly while writing and publication of the sheet. The company reserves the right to change the specifications of this product at any time withour piror notice to third parties.