

Technical Data

| Attributes | Standard | Result |
|---------------------------------|--|--|
| Type of floor covering | | Hybrid / Rigid Core |
| Installation | | 5G® Click |
| Core | | SPC |
| Colours | | 10 |
| Size | | 1820mm x 180mm |
| Thickness | | 7.0mm |
| Core thickness | | 5.0mm |
| Wear layer | | 0.5mm |
| Surface treatment | | PU coating |
| Backing | | 1.5mm EVA underlay |
| Packaging | | 6 Planks / pack = 1.996m ² |
| Total weight | | 10.19kg/m ² / 20.95kg per pack |
| Beveled edge | | 4 sided micro bevel |
| Classification | ISO 10874 / EN 685 ISO 10874 / EN 685 | Commercial: light Domestic: heavy |
| Reaction to fire | AS/NZ ISO9239 1-2003 | CHF: ≥11kW/m ² Smoke value: 136%.min |
| Slip resistance | AS 4586-2013 Amdt 1-2017 Appendix A | SRV 37 / P3 |
| Dimensional stability | Heat at 60°C for 24 hours | Length: -0.11% Width: -0.09% |
| Acoustic impact noise reduction | AS/NZ ISO 717.2-2004 | FIIC ^{4,5} = 66 L'nTw ³ = 43 AAAC 5 Star Rating ¹ |
| Underfloor heating | | Suitable for in-slab hydronic underfloor heating, max. 27°C |
| Environmental | ASTM D5116-17 Green Building Council of Australia Phthalate Free | Compliant for VOC Yes |
| Quartz content (wt%) | | Not detected |
| Warranty | Commercial Domestic | 10 Year wear* 25 Year wear* |

*Please refer to Terra Mater warranty information for guidance. www.terramaterfloors.com.au

¹Please refer to www.terramaterfloors.com.au for results.



5 Design
Repeat



Registered / Natural
Emboss



1.5mm
Acoustic Underlay



100%
Waterproof



Terra Mater

23-27 Rodeo Drive, Dandenong South VIC 3175 Australia | 1300 671 777 | sales@terramaterfloors.com.au | www.terramaterfloors.com.au