

Technical Data

Attributes	Standard	Result
Type of floor covering		Hybrid / Rigid Core
Installation		5G® Click
Core		SPC
Colours		10
Size		1820mm x 180mm
Thickness		7.0mm
Core thickness		5.0mm
Wear layer		0.5mm
Surface treatment		PU coating
Backing		1.5mm EVA underlay
Packaging		6 Planks / pack = 1.966m ²
Total weight		10.19kg/m ² / 20.95kg per pack
Beveled edge		4 sided micro bevel
Classification	ISO 10874 / EN 685 ISO 10874 / EN 685	Commercial: light Domestic: heavy
Reaction to fire	AS/NZ ISO9239 1-2003	CHF: ≥11kW/m ² Smoke value: 136%.min
Slip resistance	AS 4586-2013 Amdt 1-2017 Appendix A	SRV 37 / P3
Dimensional stability	Heat at 60°C for 24 hours	Length: -0.11% Width: -0.09%
Acoustic impact noise reduction	AS/NZ ISO 717.2-2004	FIIC ^{4,5} = 66 L'nTw ³ = 43 AAAC 5 Star Rating ¹
Underfloor heating		Suitable for in-slab hydronic underfloor heating, max. 27°C
Environmental	ASTM D5116-17 Green Building Council of Australia Phthalate Free	Compliant for VOC Yes
Quartz content (wt%)		Not detected
Warranty	Commercial Domestic	10 Year wear* 25 Year wear*

*Please refer to Terra Mater warranty information for guidance. www.terramaterfloors.com.au

¹Please refer to www.terramaterfloors.com.au for results.



5 Design
Repeat



Registered / Natural
Emboss



1.5mm
Acoustic Underlay



100%
Waterproof



Terra Mater

23-27 Rodeo Drive, Dandenong South VIC 3175 Australia | 1300 671 777 | sales@terramaterfloors.com.au | www.terramaterfloors.com.au