

MULTI PURPOSE PRIMER FOR ACOUSLIME FAST FLOW SELF LEVELLING COMPOUND

Low emission, dispersion primer for a wide range of applications for bonding Acouslime Fast Flow Self Levelling Compound to internal porous substrates.
For Professional Use



ADVANTAGES

- Ready to use
- Solvent free
- Low Emission
- Excellent bond
- Easy application
- Rapid drying
- High Coverage

TECHNICAL DATA at normal conditions at 20°C			
Application Temperature	Minimum 5°C to max. 35°C	Drying time	4 - 6 hours
Container size	5 kg	Touch Dry	15 - 20 minutes
Coverage per Container	Approx 12m ² per litre	Shelf life	12 months in original sealed container at temperature greater than 5°C Frost Sensitive
Applicator	Fine pored foam roller		

AREAS OF APPLICATION

Suitable for a wide range of sound existing absorbent substrates for interior use.

SUBSTRATE PREPARATION

The substrate must be in good condition. Must be solid, smooth, free from dust, oils and surface contaminants. All defective host on subfloor must be removed before application. Concrete substrates must be even, resistant to pressure and without dust and moisture. Any cracks must be rectified. Surface must be free from paint, oil, grease wax and solvent markers. Check moisture levels in slab in accordance with flooring to be laid.

APPLICATION

Stir the container thoroughly to disperse any clumps that may be present. Apply with a fine pored foam roller in a full even coat. Allow to dry to a clear transparent, almost tack free film. Dependant on floor temperature and humidity, in favourable climatic conditions on absorbent surfaces, a drying time of 1 – 3 hours is normally adequate. The product should be protected from frost and direct light during transportation.

CLEAN UP

Clean equipment immediately with water with water.
To remove primer that has dried on tools use mineral spirits.

SAFETY INFORMATION

The end-user of this product must first read the latest version of the Safety Data Sheets at www.acouslime.com.au before this product can be used.

DISPOSAL

Keep out of sewer and stormwater lines. In the interest of the environment, please dispose of empty containers responsibly and materials as trade waste in accordance with local authority guidelines. Do not contaminate local waterways.

[To be read in conjunction with the Safety Data Sheet](#)

DISCLAIMER Version – June 2024 The end use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven to be faulty. The manufacturer is NOT responsible for any loss or damage arising from incorrect usage of this product. The information contained herein is provided in good faith and to best of Acouslime Pty Ltd knowledge is true and accurate. No warranty is implied or given as to its completeness or accuracy in describing the performance or suitability of the product for an application
To be read in conjunction with the Safety Data Sheet