## **Technical Data**

| Attributes                                 | Result  |
|--|---|
| Species                                    | European Oak  |
| Size (L x W x Thickness/top) mr            | n 1900mm x 190mm x 14mm/3mm   |
| Locking system                             | 5G Välinge  |
| Pattern                                    | 1 strip   |
| Core                                       | 3-layer construction with SPF core  |
| Edging                                     | Micro bevelled  |
| Pack size                                  | 2.888m <sup>2</sup>   |
| Pack weight                                | 26.60kg   |
| Pack length                                | 1900mm, 8 boards per pack, up to 25% nesting  |
| Top layer (lamella)                        | 3mm European oak  |
| Surface finish                             | Klumpp 8% matte UV lacquer  |
| Installation                               | Floating / Direct stick   |
| Adhesive                                   | Swedish Dynea   |
|  |   |
| Installation Methods                       |   |
| Fully bonded                               | Yes*  |
| Nailed                                     | No  |
| Floated underlay                           | Yes*  |
| Over under slab heating                    | Yes**   |
| Subject to compatible subfloor and correct | nstallation (refer installation instructions). **Suitable for in-slab hydronic underfloor heating, max. 27°C. |
| <b>Test Information &amp; Others</b>       |   |
| Origin                                     | Europe  |
| EUTR                                       | Legally harvested timber  |
| FSC  | Not available   |
| Janka hardness rating                      | 1360 LBF (7.0)  |
|  |   |

| Slip testing                        | AS/NZS 4586-2004 Wet: P3, Dry: D1                           |
|-------------------------------------|---|
| Australian reaction to fire (Floor) | ASISO 9239-1:2003 CRF 3.6kwm <sup>2</sup> , smoke value 19% |
| Australian reaction to fire (Wall)  | AS/NZS 3837:1998 58.3kw/m <sup>2</sup>                      |
| Cigarette burns                     | Repairable  |
| Release of formaldehyde             | ASTM D51166 0.093mg/m²/hr (max limit allowable 0.1)         |
| Release of 4-phenylcyclonexene      | ASTM D5116 <0.004mg/m²/hr (max limit allowable 0.05)        |
| Total VOC                           | ASTM D5116 0.016mg/m²/hr (max limit allowable 0.5mg/m²/hr)  |
| Environmental rating                | A+. Green Building Council of Australia: Pass               |
| Warranty (Domestic)                 | 20 Year wear and lifetime structural                        |
| Warranty (Commercial)               | 5 Year wear and lifetime structural                         |

## Installation & Warranty

Please note that the technical sheet was prepared by Terra Mater Pty Ltd. All information provided was accurate at the time of publication. Terra Mater reserves the right to modify product specifications at any time without prior notice to third parties.

It is highly recommended that all WildOak floors are installed by a qualified and experienced installer. The product must be installed in full compliance with the latest WildOak installation instructions. The WildOak warranty is valid only for floors installed according to the official guidelines, which are included in every package and available on the Terra Mater website www.terramaterfloors.com.au.



WildOa

BY TERRA MATER

Arlo

k