## **Technical Data**

Attributes	Result
Species	European Oak
Size (L x W x Thickness/top) mm	1900mm x 190mm x 15mm/3mm
Locking system	Tongue & Groove
Pattern	1 strip
Core	Multiply core
Edging	Micro bevelled
Pack size	2.888m <sup>2</sup>
Pack weight	30.60kg
Pack length	1900mm, 8 boards per pack, up to 25% nesting
Top layer (lamella)	3mm European oak
Surface finish	Treffert 8% matte UV lacquer
Installation	Floating / Direct stick
Adhesive	Franklin
Installation Methods	
Fully bonded	Yes*
Nailed	No
Floated underlay	Yes*
Over under slab heating	Yes**
Subject to compatible subfloor and correct insta	, Illation (refer installation instructions). **Suitable for in-slab hydronic underfloor heating, max. 27°C.
Test Information ? Others	
Test Information & Others	
Origin	Europe
EUTR	Legally harvested timber
FSC	Not available

Not available
1360 LBF (7.0)
AS/NZS 4586-2004 Wet: P3, Dry: D1
ASISO 9239-1:2003 CRF 3.6kwm², smoke value 19%
AS/NZS 3837:1998 58.3kw/m <sup>2</sup>
Repairable
ASTM D51166 0.093mg/m²/hr (max limit allowable 0.1)
ASTM D5116 <0.004mg/m²/hr (max limit allowable 0.05)
ASTM D5116 0.016mg/m²/hr (max limit allowable 0.5mg/m²/hr)
A+. Green Building Council of Australia: Pass
20 Year wear and lifetime structural
5 Year wear and lifetime structural

## Installation & Warranty

Please note that the technical sheet was prepared by Terra Mater Pty Ltd. All information provided was accurate at the time of publication. Terra Mater reserves the right to modify product specifications at any time without prior notice to third parties.

It is highly recommended that all WildOak floors are installed by a qualified and experienced installer. The product must be installed in full compliance with the latest WildOak installation instructions. The WildOak warranty is valid only for floors installed according to the official guidelines, which are included in every package and available on the Terra Mater website www.terramaterfloors.com.au.



WildOak

BY TERRA MATER

Odo