

Technical Data

Attributes	Standard	Result
Type of floor covering		Hybrid / Rigid Core
Installation		5G® Click
Core		SPC
Colours		10
Size		1820mm x 225mm
Thickness		9.7mm
Core thickness		7.0mm
Wear layer		0.7mm
Surface treatment		PU coating
Backing		2.0mm EVA underlay
Packaging		4 Planks / pack = 1.638m ²
Total weight		14.71kg/m ² / 24.10kg per pack
Beveled edge		4 sided micro bevel
Classification	ISO 10874 / EN 685 ISO 10874 / EN 685	Commercial: heavy Domestic: very heavy
Reaction to fire	AS/NZ ISO9239 1-2003	CHF: 9.3kW/m ² Smoke value: 207%.min
Slip resistance	AS 4586-2013 Amdt 1-2017 Appendix A	SRV 37 / P3
Dimensional stability	Heat at 60°C for 24 hours	Length: -0.15% Width: -0.15%
Acoustic impact noise reduction	AS/NZ ISO 717.2-2004	FIIC ^{4,5} = 64 L'nTw ³ = 38 AAAC 6 Star Rating ¹
Underfloor heating		Suitable for hydronic underfloor heating, max. 27°C
Environmental	ASTM D5116-17 Green Building Council of Australia Phthalate Free	Compliant for VOC Yes
Quartz content (wt%)		Not detected
Warranty	Commercial Domestic	15 Year wear* 30 Year wear*

*Please refer to Terra Mater warranty information for guidance. www.terramaterfloors.com.au

¹Please refer to www.terramaterfloors.com.au for results.

Please note that the technical sheet was prepared by Terra Mater Pty Ltd. All information provided was accurate at the time of publication. Terra Mater reserves the right to modify product specifications at any time without prior notice to third parties. It is highly recommended that all ResiPlank Hybrid floors are installed by a qualified and experienced installer. The product must be installed in full compliance with the latest ResiPlank Hybrid installation instructions. The ResiPlank Hybrid warranty is valid only for floors installed according to the official guidelines, which are included in every package and available on the Terra Mater website www.terramaterfloors.com.au.

