

Attributes	Result
Species	European Oak
Size (L x W x Thickness) mm	1900mm x 190mm x 14mm/2mm
Locking system	5G Valinge
Pattern	1 strip
Core	Multiply core
Edging	4 sided micro bevel
Pack size	2.888m ²
Pack weight	27.50kg
Pack length	1900mm
Top layer (lamella)	2mm European Oak
Surface finish	Klump 8% matte UV lacquer
Installation	Floating / Direct stick
Adhesive	Swedish Dynea

Installation Methods	
Fully bonded	Yes*
Nailed	No
Floated underlay	Yes*
Over under slab heating	Yes**

*Subject to compatible subfloor and correct installation (refer installation instructions). **Suitable for in-slab hydronic underfloor heating, max. 27°C.

Test Information & Others	
Origin	Europe
EUTR	Legally harvested timber
PEFC	Certified
Janka hardness rating	7.0
Slip testing	AS/NZS 4586-2.13 D1, friction result = 0.59
Australian reaction to fire (Floor)	AS/ISO 9239-1:2003 CRF: 3.6kw/m ² , smoke value 21%
Australian reaction to fire (Wall)	AS/NZS 3837:1998 40.7kw/m ²
Cigarette burns	Repairable
Release of formaldehyde	ASTM D5116:2017 0.037mg/sqm/hr (max limit <0.1mg/m ² /hr)
Release of 4-phenylcyclonexene	AS/NZS 4266.8:2004= 0%, PASS (max limit 15%)
Total VOC	ASTM D5116:2017 0.019mg/m ² /hr (max limit <0.5mg/m ² /hr)
Environmental rating	A+ Green Building Council of Australia: Pass
Warranty (Domestic)	20 Year wear and lifetime structural
Warranty (Commercial)	5 Year wear and lifetime structural

Installation & Warranty

Please note that the technical sheet was prepared by Terra Mater Pty Ltd. All information provided was accurate at the time of publication. Terra Mater reserves the right to modify product specifications at any time without prior notice to third parties.

It is highly recommended that all WildOak floors are installed by a qualified and experienced installer. The product must be installed in full compliance with the latest WildOak installation instructions. The WildOak warranty is valid only for floors installed according to the official guidelines, which are included in every package and available on the Terra Mater website www.terramaterfloors.com.au.

