

Attributes	Result
Species	European Oak
Size (L x W x Thickness/top) mm	2200mm x 220mm x 14mm/4mm
Locking system	Tongue & Groove
Pattern	1 strip
Core	Multiply Core
Edging	4 sided micro bevel
Pack size	2.904m <sup>2</sup>
Pack weight	28.0kg
Pack length	2200mm, 6 boards per pack, up to 16% nesting per pack
Top layer (lamella)	4mm European Oak
Surface finish	Treffert 8% matte UV lacquer
Installation	Floating / Direct stick
Adhesive	Franklin

Installation Methods	
Fully bonded	Yes*
Nailed	No
Floated underlay	Yes*
Over under slab heating	Yes**

\*Subject to compatible subfloor and correct installation (refer installation instructions). \*\*Suitable for in-slab hydronic underfloor heating, max. 27°C.

Test Information & Others	
Origin	Europe
EUTR	Legally harvested timber
FSC	Certified
Janka hardness rating	1360 LBF (7.0)
Slip testing	AS/NZS 4586-2004 Wet: P3, Dry: D1
Australian reaction to fire (Floor)	ASISO 9239-1:2003 CF - 6.5kW/m <sup>2</sup> , Smoke Value 48%
VOC	ASTM D5116-25 Formaldehyde: N/D
Environmental rating	A+. Green Building Council of Australia: Pass
Warranty (Domestic)	20 Year wear and lifetime structural
Warranty (Commercial)	5 Year wear and lifetime structural

## Installation & Warranty

Please note that the technical sheet was prepared by Terra Mater Pty Ltd. All information provided was accurate at the time of publication. Terra Mater reserves the right to modify product specifications at any time without prior notice to third parties.

It is highly recommended that all WildOak floors are installed by a qualified and experienced installer. The product must be installed in full compliance with the latest WildOak installation instructions. The WildOak warranty is valid only for floors installed according to the official guidelines, which are included in every package and available on the Terra Mater website [www.terramaterfloors.com.au](http://www.terramaterfloors.com.au).

**Odo**      **Odo Herringbone**      **Soleil**      **Arlo**      **Arlo Herringbone**      **Donato**

